



RV 10 digital V

The RV 10 digital represents the continual enhancement of the IKA RV 10 Rotary Evaporator line. The unit comes with a new universal heating bath, vertical glassware, state-of-the-art safety features and digital connectivity. The RV 10 digital is a robust and reliable lab companion. Its optimized bath volume allows for fast heat-up times. The condenser unit has special designed glass tubes that utilize the 1500 cm² surface extremely efficient. That's why the RV 10 digital delivers reliable and reproducible process results that are usually reserved for more costly systems. Additional features such as smooth start, left-right interval or timer function capability support the user in their daily lab work. Another important aspect of the RV 10 digital are the sophisticated safety features. The motorized lift has an automated lift-out function in case of power outage to prevent superheating of the solvent. Safety temperature circuits can be set individually. Dry-run protection, adjustable lower end stop and lock function of bath setting complete the line of safety features. Furthermore, IKA offers a choice of coated glassware for increased safety needs. The RS 232 interface allows for remote control via IKAs "labworldsoft". The Heating bath is controlled via the IR interface from the main unit.

- Universal water/oil heating bath
- Vertical Glassware
- Motorized lift with "safety-stop" function
- RS 232 and IR Interface
- Optimized heating bath volume for fast heat-up
- Highly efficient 1500 cm² condenser unit
- Rugged design
- Ergonomically placed handles on Heating bath
- Smooth start
- Left-right interval
- Timer function
- Dry-run protection
- Safety temperature circuits
- Lower-end stop
- Choice of coated glassware
- Push-off mechanism to loosen tight fitted glassware
- Easy and safe operation due to ergonomical design of the user interface

Package description: With heating bath HB 10 and RV 10.1 Set of glassware, vertical

Technical Data	
Type of cooling	vertical
Cooling surface [cm ²]	1500
Motor principle	DC
Speed range [rpm]	20 - 280
Reversible direction of rotation	yes
Lift	Motor
Stroke [mm]	140
Heating temperature range [°C]	Room temp. - 180
Heat output [W]	1300
Set temperature resolution [±K]	1
Filling volume max. [l]	3
Timer	yes
Dimensions (W x H x D) [mm]	500 x 430 x 410
Weight [kg]	20
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 20
RS 232 interface	yes
Voltage [V]	220 - 240 / 115 / 100 - 240 / 100 - 120 / 100 - 115
Frequency [Hz]	50/60
Power input [W]	1400

Ident. No. 0008040300

Accessories: HB 10.1 Shield, HB 10.2 Protective cover, RV 10.1 Glassware vertical, RV 10.900 Glassware vertical, RV 10.3 Vertical-intensive condenser with manifold, RV 10.30 Vertical-intensive condenser with manifold, coated, RV 10.4 Dry Ice Condenser, RV 10.40 Dry Ice Condenser, coated, RV 10.5 Vertical condenser with manifold and cut-off valve for reflux distillation, RV 10.50 Vertical condenser with manifold and cut-off valve for reflux distillation, coated, RV 10.6 Vertical-intensive condenser with manifold and cut-off valve for reflux distillation, RV 10.60 Vertical-intensive condenser with manifold and cut-off valve for reflux distillation, coated, RV 05.10 Balljoint clamp, RV 10.70 Vapor tube (NS 29/32), RV 10.73 Vapor tube (NS 24/40), RV 10.80 Evaporation flask (NS 29/32, 50 ml), RV 10.2007 Evaporation flask (NS 24/40, 50 ml), RV 10.81 Evaporation flask (NS 29/32, 100 ml), RV 10.2008 Evaporation flask (NS 24/40, 100 ml), RV 10.82 Evaporation flask (NS 29/32, 250 ml), RV 10.2009 Evaporation flask (NS 24/40, 250 ml), RV 10.83 Evaporation flask (NS 29/32, 500 ml), RV 10.2010 Evaporation flask (NS 24/40, 500 ml), RV 10.84 Evaporation flask (NS 29/32, 1.000 ml), RV 10.2011 Evaporation flask (NS 24/40, 1.000 ml), RV 10.840 Evaporation flask, coated, (NS 29/32, 1.000 ml), RV 10.85 Evaporation flask (NS 29/32, 2.000 ml), RV 10.2012 Evaporation flask (NS 24/40, 2.000 ml), RV 10.86 Evaporation flask (NS 29/32, 3.000 ml), RV 10.2013 Evaporation flask (NS 24/40, 3.000 ml), RV 10.300 Powder flask (NS 29/32, 500 ml), RV 10.2017 Powder flask (NS 24/40, 500 ml), RV 10.301 Powder flask (NS 29/32, 1.000 ml), RV 10.2018 Powder flask (NS 24/40, 1.000 ml), RV 10.302 Powder flask (NS 29/32, 2.000 ml), RV 10.2019 Powder flask (NS 24/40, 2.000 ml), RV 10.400 Evaporation cylinder (NS 29/32, 500 ml), RV 10.400 Evaporation cylinder (NS 24/40, 500 ml), RV 10.401 Evaporation cylinder (NS 29/32, 1.500 ml), RV 10.401 Evaporation cylinder (NS 24/40, 1.500 ml), RV 10.500 Foam brake (NS 29/32), RV 10.2025 Foam brake (NS 24/40), RV 10.600 Distilling spider with 6 distilling sleeves (NS 29/32), RV 10.2029 Distilling spider with 6 distilling sleeves (NS 24/40), RV 10.601 Distilling spider with 12 distilling sleeves (NS 29/32), RV 10.2030 Distilling spider with 12 distilling sleeves (NS 24/40), RV 10.602 Distilling spider with 20 distilling sleeves (NS 29/32), RV 10.602 Distilling spider with 20 distilling sleeves (NS 24/40), RV 10.606 Distilling spider with 5 flasks 50 ml (NS 29/32), RV 10.2034 Distilling spider with 5 flasks 50 ml (NS 24/40), RV 10.607 Distilling spider with 5 flasks 100 ml (NS 29/32), RV 10.2035 Distilling spider with 5 flasks 100 ml (NS 24/40), RV 10.100 Receiving flask (KS 35/20, 100 ml), RV 10.101 Receiving flask (KS 35/20, 250 ml), RV 10.102 Receiving flask (KS 35/20, 500 ml), RV 10.103 Receiving flask (KS 35/20, 1.000 ml), RV 10.104 Receiving flask (KS 35/20, 2.000 ml), RV 10.105 Receiving flask (KS 35/20, 3.000 ml), RV 10.200 Receiving flask, coated (KS 35/20, 100 ml), RV 10.201 Receiving flask, coated (KS 35/20, 250 ml), RV 10.202 Receiving flask, coated (KS 35/20, 500 ml), RV 10.203 Receiving flask, coated (KS 35/20, 1.000 ml), RV 10.204 Receiving flask, coated (KS 35/20, 2.000 ml), RV 10.205 Receiving flask, coated (KS 35/20, 3.000 ml), RV 10.3000 Extension plate, RV 10.8001 Seal, PC 1.1 Cable, labworldsoft®, RV 10.5003 Pressure control valve, RV 10.5005 Set of hoses, RC 2 basic, RC 2 control, HBR 4 control, H 11 Mains cable Euro plug, VC 10 Vacuum controller, H 11 Mains cable USA plug, H 11 Mains cable CH plug, H 11 Mains cable UK plug