

IKА

designed for scientists



EUROSTAR 100 control P4

/// Data Sheet

Technical Data

Stirring quantity max. per stirring position (H ₂ O) [l]	100
Motor rating input [W]	174
Motor rating output [W]	142
Motor principle	Brushless DC
Speed display	TFT

Speed range [rpm]	10 - 300
Reversible direction of rotation	yes
Intermittent operation	yes
Viscosity max. [mPas]	100000
Output max. at stirring shaft [W]	100
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	320
Speed control	stepless
Setting accuracy speed [\pm rpm]	1
Deviation of speed measurement n < 300rpm [\pm rpm]	3
Stirring element fastening	chuck
Connection for ext. temperature sensor	PT1000
Temperature display	yes
Chuck range diameter [mm]	0.5 - 10
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	220
Torque display	yes
Nominal torque [Nm]	3.20
Torque measurement	trend
deviation of torque measurement I [\pm Ncm]	30
Timer	yes
Timer display	TFT
Time setting range [min]	1 - 6000
Temperature measuring range [°C]	-10 - +350
Temperature measurement resolution [K]	0.1
Accuracy of temperature measurement [K]	$\pm 0.5 + \text{tolerance PT1000 (DIN IEC 751 Class A)}$
Limit deviation temperature sensor [K]	$\leq \pm (0.15 + 0.002 \times \text{ITI})$
housing material	alu-cast coating / thermoplastic polymer
communication distance (depend onbuilding) max. [m]	150
Dimensions (W x H x D) [mm]	86 x 352 x 230
Weight [kg]	5.2
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 40
USB interface	yes
RS 232 interface	yes
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	150