



designed for scientists



## EUROSTAR 60 control

/// Data Sheet

Universal laboratory stirrer designed with a removable wireless controller and a digital TFT display. It automatically adjusts the speed through microprocessor controlled technology within the speed range of 0/30 - 2000 rpm. The stirrer comes equipped with a RS 232 and a USB interface to control and document all parameters. An integrated torque trend display is provided for the measurement of viscosity changes. Safety circuits installed ensures automatic cut-off in an anti-stall or overload conditions. Continuous comparison of shaft speed to desired speed is maintained and variations are adjusted automatically. This guarantees a constant speed even with changes in viscosities of the sample.

- Multilingual TFT display



designed for scientists

- Programmable functions
- Integrated temperature measurement
- Interval operation
- Timer function
- Adjustable safety circuit
- Locked function
- Infinitely adjustable speed
- Push-through agitator shafts
- Overload protection
- Short-term overload operation
- Slim casing
- Quiet operation
- Error code display
- H 67.60 temperature sensor and WH 11 WiCo holder included in delivery

### Technical Data

|   |               |
|---|---------------|
| Stirring quantity max. per stirring position (H2O) [l]    | 40            |
| Motor rating input [W]                                    | 168           |
| Motor rating output [W]                                   | 131           |
| Motor principle   | Brushless DC  |
| Speed display   | TFT           |
| Speed range [rpm]   | 0/30 - 2000   |
| Intermittent operation                                    | yes           |
| Viscosity max. [mPas]                                     | 50000         |
| Output max. at stirring shaft [W]                         | 126           |
| Permissible ON time [%]                                   | 100           |
| Torque max. at stirring shaft [Ncm]                       | 60            |
| Speed control   | stepless      |
| Setting accuracy speed [ $\pm$ rpm]                       | 1             |
| Deviation of speed measurement $n > 300$ rpm [ $\pm$ %]   | 1             |
| Deviation of speed measurement $n < 300$ rpm [ $\pm$ rpm] | 3             |
| Stirring element fastening                                | chuck         |
| Connection for ext. temperature sensor                    | PT1000        |
| Temperature display                                       | yes           |
| Chuck range diameter [mm]                                 | 0.5 - 10      |
| Hollow shaft, inner diameter [mm]                         | 11            |
| Hollow shaft (push-through - when stopped)                | yes           |
| Fastening on stand  | extension arm |
| Extension arm diameter [mm]                               | 16            |
| Extension arm length [mm]                                 | 220           |
| Torque display  | yes           |
| Speed control   | electronic    |
| Nominal torque [Nm]                                       | 0.6           |
| Torque measurement  | trend         |
| deviation of torque measurement I [ $\pm$ Ncm]            | 6             |
| Timer   | yes           |
| Timer display   | TFT           |



designed for scientists

|   |   |
|---|---|
| Time setting range [min]                            | 1 - 6000                                      |
| Temperature measuring range [°C]                    | -10 - +350                                    |
| Temperature measurement resolution [K]              | 0.1   |
| Accuracy of temperature measurement [K]             | ±0.5 + tolerance PT1000 (DIN IEC 751 Class A) |
| Limit deviation temperature sensor [K]              | ≤ ± (0.15 + 0.002x T )                        |
| housing material                                    | alu-cast coating / thermoplastic polymer      |
| communication distance (depend onbuilding) max. [m] | 150   |
| Dimensions (W x H x D) [mm]                         | 86 x 267 x 230                                |
| Weight [kg]   | 4.7   |
| Permissible ambient temperature [°C]                | 5 - 40  |
| Permissible relative humidity [%]                   | 80  |
| Protection class according to DIN EN 60529          | IP 40   |
| RS 232 interface                                    | yes   |
| USB interface                                       | yes   |
| Voltage [V]   | 230 / 115 / 100                               |
| Frequency [Hz]                                      | 50/60   |
| Power input [W]                                     | 176   |