

Data Sheet

MHD-Plant 2000/05



MHD-Plant 2000/05

The IKA mixing plant MHD essentially consists of the patented IKA inline mixing machine MHD, metering units, an electrical control system and a periphery which is customized to fit the customer's application. The MHD plant enables the dust-free mixing of liquids and solids (powders or granules) in a continuous process. The phases to be mixed are fed into the MHD machine in proportion to quantity, then mixed in the working chamber and subsequently dispersed, allowing for a ready final product to be produced in just one passage.

The plant is able to process solids contents of up to 80% and mixtures with viscosities of up to 50,000 mPas. The continuously working MHD plant amortizes itself very quickly when it comes to particularly large production quantities. The funds invested into dosing are considerably lower than the purchasing costs for holding tanks and the appropriate mixing vessels with stirrers. Furthermore, the MHD plant offers great flexibility as any product quantities can be produced with a constant quality.

For simple applications, the dosing of the solid is carried out by means of a volumetric metering unit. The dosing output is dependent on the volume transport per time unit and remains steady by processing with the same bulk density and an even filling into the dosing device. Whenever a higher dosing precision is required or difficult substances are conveyed, gravimetric metering devices come into operation. The varying solids, and therefore the dosing amounts, are measured by one or more scales, compared to the previously set target quantities and automatically adjusted by means of a controlled drive system in case of deviations. Changing the bulk weight or the material characteristics does not affect the dosing results. Therefore, a concentration precision of up to 0.5 mass percentage or better is possible.

As for electric control of the plant, different versions are available, depending on customer demands:

Manual control: Essential, safety-relevant locking devices are put into effect. Flow rate is controlled via simple potentiometers.

Automatic control: The control system allows for a defined sequence to be run in automatic mode. After starting, the plant runs automatically until it is shut down either manually, by means of an external signal or due to a breakdown.

Recipe management: Recipes can be compiled, changed and archived by means of a process control system.

Technical Data

Process temperature, min.	-10 °C
Process temperature, max.	125 °C
Viscosity, max.	50 Pas
Total capacity to	750 l/h
Motor power MHD	5.5 kW
Total power input	7.5 kW
Solids capacity (depending on bulk-density) to	180 l/h
Mixing machine	MHD 2000/05
Pipe connections	DIN 11851
Inlet for liquids, MHD	DN 25
Inlet for solids, MHD	DN 50
Outlet mixture, MHD	DN 32

Ident. No. 000MHD-Plant2000/05

The IKA MHD mixing plants are manufactured in seven different sizes ranging from lab and pilot plants to production plants with an overall throughput of 40,000 l/h. The supply scope of the MHD plant conforms to your inquiry. Devices for powder feeding such as sack emptying machines and big bag stations, systems for conveying of the final mixture, buffer vessels, IKA machines for fine milling and other peripheries can all be installed into the production line. Per request, our services can also include the on-site assembly of the plant, commissioning and training for your personnel. Getting the whole system from one source will allow for you to have just one contact person for your entire project.